

Material security data sheet

Printed : 03/02/2022

Revised : 001NEW21-1-CLP from 03/02/2022

PARSLEY LEAF ESS OIL

1. PRODUCT AND COMPANY IDENTIFICATION

1.1. Product identifier

PARSLEY LEAF ESS OIL

C.A.S Number : 8000-68-8 ; ;
C.A.S EINECS Number : 84012-33-9
C.A.S (TSCA) :
EINECS Number : 281-677-1
EC Number :
REACH Registration n° : Exempted (manufactured or imported <1T/year)

1.2. Relevant identified uses of the substance or mixture and uses advised against

Concentrated aromatic raw material.
Not intended for personal use in this form or concentration.
For industrial use only, not for retail sale.

USE : **Perfuming substance ; flavouring substance (according to batches)**

1.3. Details of the supplier of the safety data sheet

Company : SAS DIFFUSIONS AROMATIQUES
558 allée des Parfums
Parc d'activités "Les Hauts de Grasse"
06530 SAINT-CEZAIRE-SUR-SIAGNE
Tel:+33 (0)4 93 60 82 82
Fax :+33 (0)4 93 60 82 79
Web :www.diffusions-aromatiques.fr
Email :contact@diffusions-aromatiques.fr

1.4. Emergency telephone number

Emergency telephone number 24h/24 - 7d/7: ORFILA (INRS) : +33.(0)1.45.42.59.59

2. HAZARD IDENTIFICATION

2.1. Classification of the substance or mixture

Classification :

(RegulationCLP)

AH1 Aspiration hazard 1
ED12 Serious eye damage / eye irritation 2
EHA1 Hazardous to the aquatic environment, acute hazard 1
EHC2 Hazardous to the aquatic environment, long-term hazard 2
FL3 Flammable Liquids 3
SCI2 Skin corrosion / irritation 2
SS1 Sensitisation skin 1

H226 - Flammable liquid and vapour.

Material security data sheet

Printed : 03/02/2022

PARSLEY LEAF ESS OIL


Revised : 001NEW21-1-CLP from 03/02/2022

H304 - May be fatal if swallowed and enters airways.
 H315 - Causes skin irritation.
 H317 - May cause an allergic skin reaction.
 H319 - Causes serious eye irritation.
 H400 - Very toxic to aquatic life.
 H411 - Toxic to aquatic life with long lasting effects.

2.2. Label elements

Classification :

(RegulationCLP)



Warning mention : Danger

AH1 Aspiration hazard 1
 EDI2 Serious eye damage / eye irritation 2
 EHA1 Hazardous to the aquatic environment, acute hazard 1
 EHC2 Hazardous to the aquatic environment, long-term hazard 2
 FL3 Flammable Liquids 3
 SCI2 Skin corrosion / irritation 2
 SS1 Sensitisation skin 1

H226 - Flammable liquid and vapour.
 H304 - May be fatal if swallowed and enters airways.
 H315 - Causes skin irritation.
 H317 - May cause an allergic skin reaction.
 H319 - Causes serious eye irritation.
 H400 - Very toxic to aquatic life.
 H411 - Toxic to aquatic life with long lasting effects.

P264 - Wash ... thoroughly after handling.
 P273 - Avoid release to the environment.
 P301+P310 - IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.
 P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
 P331 - Do NOT induce vomiting.
 P332+P313 - If skin irritation occurs: Get medical advice/attention.

2.3. Other hazards

Contains alpha-Pinene, Terpinolene, Myrcene, Beta-phellandrene, Beta pinene, Limonene, Camphene, Estragole

No information available.

3. COMPOSITION / INFORMATION ON INGREDIENT

3.1. Components

Material	C.A.S	EINECS	Risk Symbol	Percent %
----------	-------	--------	-------------	-----------

Material security data sheet

Printed : 03/02/2022

PARSLEY LEAF ESS OIL

Revised : 001NEW21-1-CLP from 03/02/2022

alpha-Pinene	80-56-8	201-291-9	AH1, ATO4, EHA1, EHC1, FL3, SCI2, SS1B - H226, H302, H304, H315, H317, H400, H410	[20-30]
Beta pinene	127-91-3		AH1, EHA1, EHC1, FL3, SCI2, SS1B - H226, H304, H315, H317, H400, H410	[5-10]
Beta-phellandrene	555-10-2	209-081-9	AH1, FL3 - H226, H304	[5-10]
Myrcene	123-35-3	204-622-5	AH1, EDI2, EHA1, EHC2, FL3, SCI2 - H226, H304, H315, H319, H400, H411	[5-10]
Terpinolene	586-62-9	209-578-0	AH1, EHA1, EHC1, SS1B - H317, H400, H410	[5-10]
Limonene	5989-27-5	227-813-5	AH1, EHA1, EHC2, FL3, SCI2, SS1B - H226, H304, H315, H317, H411	[5-10]
Camphene	79-92-5	201-234-8	EDI2, EHC1 - H319, H410	[0.1-1]
Estragole	140-67-0	205-427-8	ATO4, CAR2, EDI2, EHC3, MUT2, SCI2, SS1A - H302, H315, H317, H319, H341, H351, H412	[0.1-1]
l-Carvone	6485-40-1	229-352-5	SS1B - H317	[0.1-1]
Linalool	78-70-6	201-134-4	EDI2, SCI2, SS1B - H315, H317, H319	< 0.1 %

3.2. Description

BOTANICAL NAME : **Petroselinum crispum**

4. FIRST AID MEASURES

4.1. Description of first aid measures

General notes: Take Risk and Safety phrases (section 15) into account.

Following inhalation:

Remove from exposure site to fresh air and keep at rest. Obtain medical advice.

Following skin contact:

Remove contaminated clothes. Wash thoroughly with water (and soap). Contact physician if symptoms persist.

Following eye contact:

Flush immediately with water for at least 15 minutes. Contact physician if symptoms persist.

Following ingestion:

Rinse mouth with water and obtain medical advice.

Notes for the doctor:

Treat symptomatically and supportively.

Treatment may vary with condition of victim and specifics of incident.

4.2. Most important symptoms and effects, both acute and delayed

It presents no significant acute and delayed symptoms.

4.3. Indication of any immediate medical attention and special treatment needed

Attending physician should treat exposed patients symptomatically

Material security data sheet

Printed : 03/02/2022

PARSLEY LEAF ESS OIL

Revised : 001NEW21-1-CLP from 03/02/2022

Contact with skin : wash immediately and abundantly with water and soap. Rinse then with clear water.
Contact with eyes : Abundant rinsing with water (15 minutes open eyelids) then washing with an ocular lotion standard Dacryoserum. In case of disorder, consult an ophthalmologist.
In the event of swallowed : Not make vomit, maintain the patient at rest. Resort to the medical care.
Soiled clothing : withdraw soiled clothing and re-use them only after decontamination.
Persons with pre-existing skin, eye, or respiratory disease may be at increased risk from the irritant or allergic properties of this material.

5. FIRE FIGHTING

5.1. Extinguishing media

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

5.2. Special hazards arising from the substance or mixture

Flammability : The product is not flammable..
Prévention: Do not smoke. Do not use flame near.

5.3. Advice for firefighters

Never use a direct stream of water.

6. ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Use individual protective equipment (waterproof boots, suitable protective clothing, and safety glasses). Prevent any contact with hot surfaces. Do not approach facing the wind. Ensure adequate ventilation. Do not breathe vapour/spray.

6.2. Environmental precautions

Do not allow to enter sewers/ surface or ground water.

6.3. Methods and material for containment and cleaning up

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

6.4. Reference to other sections

See Section 7 for information on safe handling.
See section 8 for information on personal protection equipment.
See Section 13 for information on disposal

7. HANDLING AND STORAGE

7.1. Precautions for safe handling

Material security data sheet

Printed : 03/02/2022

PARSLEY LEAF ESS OIL

Revised : 001NEW21-1-CLP from 03/02/2022

Advice on safe handling: Avoid excessive inhalation of concentrated vapors. Follow good manufacturing practices for housekeeping and personal hygiene. Wash any exposed skin immediately after any chemical contact, before breaks and meals, and at the end of each work period. Contaminated clothing and shoes should be thoroughly cleaned before re-use.

If appropriate, procedures used during the handling of this material should also be used when cleaning equipment or removing residual chemicals from tanks or other containers, especially when steam or hot water is used, as this may increase vapor concentrations in the workplace air. Where chemicals are openly handled, access should be restricted to properly trained employees.

Keep all heated processes at the lowest necessary temperature in order to minimize emissions of volatile chemicals into the air.

Advice on protection against fire and explosion: Keep away from ignition sources and naked flame. Close packing after use. Reproduce labelling if transfer in another container.

7.2. Conditions for safe storage, including any incompatibilities

-Avoid any useless exposure. Keep away from food and drinks.

-Preserve only in the container of origin in a fresh place and broken down well. Keep the containers closed out of their use.

-Do not leave it near heat source, direct rays of the sun

7.3. Specific end use(s)

Not available

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

8.1. Control parameters

NO CONCERNED

8.2. Exposure controls

General protective and hygienic measures: Avoid skin and eyes contact. Keep away from foodstuffs, beverages and feed. Wash hands before breaks and at the end of work.

Personal Protection :

- Hand protection: Wear gloves.
- Eye protection: Wear glasses.
- Respiratory protection : Wear a mask.
- Ingestion : Do not use, drink and smoke during use.

Eye and face protection: Use tight-fitting goggles, face shield or safety glasses with side shields if eye contact might occur.

Skin protection: Wear appropriate dust resistant clothing. Avoid skin contact. Use chemically resistant gloves.

Protective gloves: The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation.

Respiratory protection: See local exhaust ventilation around open tanks and other open sources of potential exposures in order to avoid excessive inhalation, including places where this material is openly weighed or measured.

Thermal hazards: Not available.

Environmental exposure controls: Prevent from entering sewers, basements and workpans, or any place where its accumulation can be dangerous.

Consumer exposure controls: Avoid breathing directly on the product. Apply local ventilations when

Material security data sheet

Printed : 03/02/2022

PARSLEY LEAF ESS OIL

Revised : 001NEW21-1-CLP from 03/02/2022

appropriate. Wash hands with soap and water after handling.

9. PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

Shelf life :	24 months in below conditions, after this time it can be used after control.
FREEZING POINT :	ND
POINT D'INFLAMMATION :	ND
IGNITION TEMPERATURE (°C) :	ND
EXPLOSIVE LIMITS :	ND
Appearance :	Liquid
Color :	Pale yellow to yellow
ODOR :	Characteristic
Relative density (d ₂₀ /20) :	[0.910 ; 0.950]
Refractive index to 20°C :	[1.500 ; 1.520]
Solubility(ies) :	Insoluble in water, soluble in ethanol
Flash point :	46°C
OPTICAL ROTATION (°) :	ND
Vapor pressure :	ND
Partition coef (n-octanol/water) :	ND
FUSION POINT (capillarity) °C :	ND
BOILING POINT (°C) :	ND
PH :	ND

9.2. Other information

NO CONCERNED

10. STABILITY AND REACTIVITY

10.1. Reactivity

· **Dangerous reactions** : No dangerous reactions known.

10.2. Chemical stability

Stable under recommended storage conditions.

10.3. Possibility of hazardous reactions

No hazardous reactions known.

10.4. Conditions to avoid

Material security data sheet

Printed : 03/02/2022

PARSLEY LEAF ESS OIL

Revised : 001NEW21-1-CLP from 03/02/2022

Avoid excessive heat for prolonged periods of time.

10.5. Incompatible materials

Avoid contact with strong acids, alkali or oxidizing agents.

10.6. Hazardous decomposition products

Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.

Dangerous decomposition products: Carbon monoxide and unidentified organic compounds may be formed during combustion.

11. TOXICOLOGICAL INFORMATION

11.1. Information on toxicological effects

Toxicological Informations Acute :

DL50 (dermal/ rat) mg/kg : **ND**

LD50 ORAL/RAT (mg/kg) : **ND**

PRESENCE of CMR : **May naturally (technically unavoidable) contain :Estragole <0,4%**

12. ECOLOGICAL INFORMATION

12.1. Toxicity

Do not leave the product, even diluted or in great quantity, penetrate the ground water, water or the drains.

12.2. Persistence and degradability

BIODEGRADABILITY : **ND**

12.3. Bioaccumulative potential

NO CONCERNED

12.4. Mobility in soil

No data available.

12.5. Results of PBT and vPvB assessment

No data available.

12.6. Other adverse effects

NO CONCERNED

Material security data sheet

Printed : 03/02/2022

PARSLEY LEAF ESS OIL

Revised : 001NEW21-1-CLP from 03/02/2022

13. DISPOSAL RECOMMENDATIONS

13.1. Waste treatment methods

Product : Recommendation : Does not have to be evacuated with the refuse . Not to let penetrate in the sewers.

Not cleaned packing : Recommendation : Evacuation in accordance with the regulations.

14. TRANSPORT INFORMATION

:



:



IATA:



14.1. UN number

: 1169 (D/E)

:1169

IATA :1169

UN N° :

1169 (extracts, aromatic, liquid)

14.2. Transport hazard class(es) and Packing group

RID/ADR (Road) :

3 III subsidiary risk HAZARDOUS TO ENVIRONMENT

IATA (Air) :

3 III

IMDG (Sea) :

3 III subsidiary risk HAZARDOUS TO ENVIRONMENT - Marine pollutant

15. REGULATORY INFORMATION

The product is not classified.

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Class of water contamination (Germany) : WGK

15.2. Chemical safety assessment

Material security data sheet

Printed : 03/02/2022

PARSLEY LEAF ESS OIL

Revised : 001NEW21-1-CLP from 03/02/2022

NO CONCERNED

16. OTHER INFORMATION

Full H sentences text in point 3 :

- H226 Flammable liquid and vapour.
H302 Harmful if swallowed.
H304 May be fatal if swallowed and enters airways.
H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.
H341 Suspected of causing genetic defects <state route of exposure if it is conclusively proven that no

other routes of exposure cause the hazard>.

- H351 Suspected of causing cancer <state route of exposure if it is conclusively proven that no other
routs

of exposure cause the hazard>.

- H400 Very toxic to aquatic life.
H410 Very toxic to aquatic life with long lasting effects.
H411 Toxic to aquatic life with long lasting effects.
H412 Harmful to aquatic life with long lasting effects.

Material security data sheet according to 2001/58/CEE.

These indications are founded on the current state of our knowledge, but do not constitute a guarantee as for the properties of the product and do not give place to a contractual legal report.

REVISION DATE :

03/02/2022